



GS BATTERY

AUTOMOTIVE BATTERY

high power

GS

PREMIUM



GS Battery
No.1

in Japan for over 100 years

Authorized Distributor



Infinitier Company Ltd.

Room 601 Bupa Centre,
141 Connaught Road West, Hong Kong
Tel: +852 2857 1793 Fax: +852 2857 1079
<http://www.infinitier.com.hk>



DRY CHARGED BATTERY SPECIFICATION (GS PREMIUM)

No	Battery Type		Capacity		CCA	Dimension (mm)				Layout	Terminal	Qty / Pallet	
	OLD JIS	NEW JIS	5 HR	20 HR(*)		L	W	H	TH			Large	Small
1	12N24R	26A19R	21	26	170	187	127	162	184	1	C	180	135
2	12N24L	26A19L	21	26	170	187	127	162	184	2	C	180	135
3	34B19R	34B19R	27	33	240	187	127	203	227	1	B	180	135
4	34B19L	34B19L	27	33	240	187	127	203	227	2	B	180	135
5	34B19RS	34B19RS	27	33	240	187	127	203	227	1	B	180	135
6	34B19LS	34B19LS	27	33	240	187	127	203	227	2	B	180	135
7	NS40	32B20R	26	32	225	197	129	203	227	1	B	168	126
8	NS40L	32B20L	26	32	225	197	129	203	227	2	B	168	126
9	NS40S	32B20RS	26	32	225	197	129	203	227	1	A	168	126
10	NS40LS	32B20LS	26	32	225	197	129	203	227	2	A	168	126
11	NS40Z	36B20R	28	35	260	197	129	203	227	1	B	168	126
12	NS40ZL	36B20L	28	35	260	197	129	203	227	2	B	168	126
13	NS40ZLS	36B20LS	28	35	260	197	129	203	227	2	A	168	126
14	NS40ZS	36B20RS	28	35	260	197	129	203	227	1	A	168	126
15	N40	32C24R	32	40	195	238	129	203	227	1	A	144	108
16	N40L	32C24L	32	40	195	238	129	203	227	2	A	144	108
17	NS60	46B24R	36	45	295	238	129	203	227	1	B	144	108
18	NS60L	46B24L	36	45	295	238	129	203	227	2	B	144	108
19	NS60S	46B24RS	36	45	295	238	129	203	227	1	A	144	108
20	NS60LS	46B24LS	36	45	295	238	129	203	227	2	A	144	108
21	55D23R	55D23R	48	60	320	232	173	204	225	1	A	112	84
22	55D23L	55D23L	48	60	320	232	173	204	225	2	A	112	84
23	75D23R	75D23R	52	65	465	232	173	204	225	1	A	112	84
24	75D23L	75D23L	52	65	465	232	173	204	225	2	A	112	84
25	N50	48D26R	40	50	250	260	173	204	225	1	A	96	72
26	N50L	48D26L	40	50	250	260	173	204	225	2	A	96	72
27	N50Z	55D26R	48	60	290	260	173	204	225	1	A	96	72
28	N50ZL	55D26L	48	60	290	260	173	204	225	2	A	96	72
29	NS70	65D26R	52	65	370	260	173	204	225	1	A	96	72
30	NS70L	65D26L	52	65	370	260	173	204	225	2	A	96	72
31	80D26R	80D26R	55	65	490	260	173	204	225	1	A	96	72
32	80D26L	80D26L	55	65	490	260	173	204	225	2	A	96	72
33	N70	65D31R	56	70	340	306	173	204	225	1	A	84	63
34	N70L	65D31L	56	70	340	306	173	204	225	2	A	84	63
35	N70Z	75D31R	60	70	380	306	173	204	225	1	A	84	63
36	N70ZL	75D31L	60	70	380	306	173	204	225	2	A	84	63
37	NX120-7R	95D31R	64	80	565	306	173	204	225	1	A	84	63
38	NX120-7L	95D31L	64	80	565	306	173	204	225	2	A	84	63
39	105D31R	105D31R	64	80	655	306	173	204	225	1	A	84	63
40	105D31L	105D31L	64	80	655	306	173	204	225	2	A	84	63
41	N100	95E41R	80	100	475	410	176	213	234	1	A	56	42
42	N100L	95E41L	80	100	475	410	176	213	234	2	A	56	42
43	NS120	115E41R	88	110	610	410	176	213	234	1	A	56	42
44	N120	115F51	96	120	575	505	182	213	257	3	A	36	36
45	N150	145G51	120	150	685	508	222	213	257	3	A	30	30
46	NS200	165G51	136	170	710	508	222	213	257	3	A	30	30
47	N200	190H52	160	200	765	521	278	220	270	3	A	24	24
48	555-65	555-65	-	55	255	246	175	190	190	1	A	96	72
49	555-59	555-59	-	55	255	246	175	190	190	2	A	96	72
50	566-38	566-38	-	66	300	299	175	190	190	2	A	84	63
51	588-27	588-27	-	88	395	381	175	190	190	2	A	56	42
52	544-59	544-59	-	44	210	202	175	190	190	2	A	100	75
53	544-64	544-64	-	44	210	208	175	190	190	1	A	100	75
54	545-19	545-19	-	45	220	240	175	175	175	2	A	100	75

(*) 20 HR capacity is based on calculation (approximately)

